

PALAX KS35 ERGO (P.T.O. DRIVEN)	
Hydraulic oil VGA 32 40 l / 10.5 G	Splitting cylinder, 8 tons (kg) / 17,600 lbs
Flow of hydraulic pump 36 l/min or 9.5 GPM	Articulated shaft at 400 r.p.m.
Automatic high-speed valve	Additional circuit for external log-deck
TRANSMISSION	
Articulated shaft, suitable size e.g. Bondioli 143	
OUTPUT	
Speed Standard: 5 sec / High-speed: 3.3 sec	
Max. diameter of log: 35 cm / 13.8 in	Cutting length: 25 to 60 cm / 10 in to 2 ft
CHAINSAW	
15" sawbar/chain driven by hydraulic motor	
Automatic lubricator, separate tank, volume 2 l / 0.5 G	
LOG SPLITTING	
Splitting wedge 2/4 as standard	Splitting wedge 2/6 or 2/8 as an option
Stepless height adjustment of the splitting wedge	
Quick-release of splitting wedge	Log-stop, gives way automatically
Debris removal grate in the splitting chute	
Control/operating levers with ball bearings	
DISCHARGE CONVEYOR	
Palax 43 scraper conveyor, length 4.3 m / 14.1 ft, with 2 chains	
Lifting winch for conveyor	Automatic tightening of the chains
Conveyor swings by 2.2 m / 7.2 ft to the side, quick-release	
IN-FEED CONVEYOR	
In-Feed conveyor 200 x 2200 mm / 7.9 x 86.6 in	
Debris removal scrapers on rollers	
DIMENSIONS AND WEIGHT	
Length, incl. conveyor 3.5 m / 11.5 ft : 2,850 mm / 9.3 ft	
Width, incl. conveyor 3.5 m / 11.5 ft : 950 mm / 3.1 ft	
Height, incl. 3.5 m / 11.5 ft conveyor : 2,390 mm / 7.8 ft	
Weight: 720 kg / 1,590 lbs	

Approximate values for all specifications.